

Chemical Safety Data Sheet MSDS / SDS

2-methylpropene SDS

Revision Date:2024-04-25 Revision Number:1

Section 1	Section 2	Section 3	Section 4	Section 5	Section 6	Section 7	Section 8
Section 9	Section 10	Section 11	Section 12	Section 13	Section 14	Section 15	Section 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product identifier**

Product name: 2-methylpropene

CAS: 115-11-7

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: For R&D use only. Not for medicinal, household or other use.

Uses advised against: none

Company Identification

Company: Chemicalbook.in

Address: 5 vasavi Layout Basaveswara Nilayam Pragathi Nagar Hyderabad, India -500090

Telephone: +91 9550333722

SECTION 2: Hazards identification**Classification of the substance or mixture**Gases under pressure: Compressed gas
Flammable gases, Category 1A, Flammable gas

GHS label elements, including precautionary statements

Pictogram(s)



Signal word

Danger

Hazard statement(s)

H220 Extremely flammable gas

Precautionary statement(s)

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

Storage

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P403 Store in a well-ventilated place.

Disposal

none

Other hazards which do not result in classification

no data available

SECTION 3: Composition/information on ingredients

Substance

Chemical name: 2-methylpropene

Common names and synonyms: 2-methylpropene

CAS number: 115-11-7
EC number: 204-066-3
Concentration: 100%

SECTION 4: First aid measures

Description of necessary first-aid measures

If inhaled

Fresh air, rest. Artificial respiration may be needed. Refer for medical attention.

Following skin contact

ON FROSTBITE: rinse with plenty of water, do NOT remove clothes. Refer for medical attention .

Following eye contact

First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.

Following ingestion

Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.

Most important symptoms/effects, acute and delayed

Inhalation of moderate concentrations causes dizziness, drowsiness, and unconsciousness. Contact with eyes or skin may cause irritation; the liquid may cause frostbite. (USCG, 1999)

Indication of immediate medical attention and special treatment needed, if necessary

Basic Treatment: Establish a patent airway. Suction if necessary. Watch for signs of respiratory insufficiency and assist ventilations if necessary. Administer oxygen by nonrebreather mask at 10 to 15 L/min. Monitor for pulmonary edema and treat if necessary ... Anticipate seizures and treat as necessary ... For eye contamination, flush eyes immediately with water. Irrigate each eye continuously with normal saline during transport ... Do not use emetics. For ingestion, rinse mouth and administer 5 mL/kg up to 200 mL of water for dilution if the patient can swallow, has a strong gag reflex, and does not drool. Administer activated charcoal ... Treat frostbite with rapid rewarming techniques ... Aliphatic hydrocarbons and related compounds

SECTION 5: Firefighting measures

Suitable extinguishing media

To fight fire, stop flow of gas.

Specific hazards arising from the chemical

Behavior in Fire: Containers may explode in fire. Vapor is heavier than air and may travel a long distance to a source of ignition and flash back. (USCG, 1999)

Special protective actions for fire-fighters

Shut off supply; if not possible and no risk to surroundings, let the fire burn itself out. In other cases extinguish with water spray, powder, carbon dioxide. In case of fire: keep drums, etc., cool by spraying with water. Combat fire from a sheltered position.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Evacuate danger area! Consult an expert! Ventilation. Remove all ignition sources. Do NOT wash away into sewer. NEVER direct water jet on liquid. Personal protection: chemical protection suit including self-contained breathing apparatus.

Environmental precautions

Evacuate danger area! Consult an expert! Ventilation. Remove all ignition sources. Do NOT wash away into sewer. NEVER direct water jet on liquid. Personal protection: chemical protection suit including self-contained breathing apparatus.

Methods and materials for containment and cleaning up

Collect and arrange disposal. Keep the chemical in suitable and closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.

SECTION 7: Handling and storage

Precautions for safe handling

NO open flames, NO sparks and NO smoking. NO contact with oxidizing agents. Closed system, ventilation, explosion-proof electrical equipment and lighting. Prevent build-up of electrostatic charges (e.g., by grounding). Use non-sparking handtools.

Handling in a well ventilated place. Wear suitable protective clothing. Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Use non-sparking tools. Prevent fire caused by electrostatic discharge steam.

Conditions for safe storage, including any incompatibilities

Fireproof. Separated from incompatible materials. See Chemical Dangers. Cool.... MATERIALS WHICH ARE TOXIC AS STORED OR WHICH CAN DECOMPOSE INTO TOXIC COMPONENTS ... SHOULD BE STORED IN A COOL, WELL VENTILATED PLACE, OUT OF THE DIRECT RAYS OF THE SUN, AWAY FROM AREAS OF HIGH FIRE HAZARD, AND SHOULD BE PERIODICALLY INSPECTED. INCOMPATIBLE MATERIALS SHOULD BE ISOLATED ...

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational Exposure limit values

TLV: 250 ppm as TWA; A4 (not classifiable as a human carcinogen)

Biological limit values

no data available

Appropriate engineering controls

Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Set up emergency exits and the risk-elimination area.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Wear face shield or eye protection in combination with breathing protection.

Skin protection

Cold-insulating gloves.

Respiratory protection

Use closed system or ventilation.

Thermal hazards

no data available

SECTION 9: Physical and chemical properties and safety characteristics

Physical state:	Gaseous.
Colour:	Colourless.
Odour:	Coal gas odor
Melting point/freezing point:	-140.7 °C. Remarks:At standard temperature and pressure.
Boiling point or initial boiling point and boiling range:	-6.9 °C. Remarks:At standard temperture and pressure.
Flammability:	Extremely flammable.
Lower and upper explosion limit/flammability limit:	no data available
Flash point:	-76 °C.
Auto-ignition temperature:	465 °C.
Decomposition temperature:	no data available
pH:	no data available
Kinematic viscosity:	no data available
Solubility:	Insoluble (NTP, 1992)
Partition coefficient n-octanol/water:	log Pow = 2.34.
Vapour pressure:	2 574 hPa. Temperature:20 °C.

Density and/or relative density:	0.59 g/cm ³ . Temperature: 25 °C.
Relative vapour density:	2 (vs air)
Particle characteristics:	no data available

SECTION 10: Stability and reactivity

Reactivity

Reacts violently with halogens, oxidants and strong acids. This generates fire and explosion hazard.

Chemical stability

Volatile liquid or easily liquefied gas.

Possibility of hazardous reactions

A very dangerous fire and explosion hazard when exposed to heat or flame. The gas is heavier than air and may travel along the ground; distant ignition possible. The gas is heavier than air and may accumulate in lowered spaces causing a deficiency of oxygen. As a result of flow, agitation, etc., electrostatic charges can be generated. ISOBUTYLENE is incompatible with oxidizers. It polymerizes easily. It reacts easily with numerous materials, such as alkyl halides, halogens, concentrated sulfuric acid, hypochlorous acid, aluminum chloride, carbon monoxide and hydrogen with a cobalt catalyst. Polymerization is catalyzed by aluminum chloride and boron trifluoride. (NTP, 1992)

Conditions to avoid

no data available

Incompatible materials

Can react vigorously with oxidizing materials.

Hazardous decomposition products

When heated to decomposition it emits acrid smoke and fumes.

SECTION 11: Toxicological information

Acute toxicity

Oral: LC50 Mouse oral 415 mg/L/2 hr

Inhalation: no data available

Dermal: no data available

Skin corrosion/irritation

no data available

Serious eye damage/irritation

no data available

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

STOT-single exposure

Rapid evaporation of the liquid may cause frostbite. The substance may cause effects on the central nervous system. Exposure at high levels could cause unconsciousness.

STOT-repeated exposure

no data available

Aspiration hazard

On loss of containment this substance can cause serious risk of suffocation when in confined areas.

SECTION 12: Ecological information

Toxicity

Toxicity to fish: LC50 - Fish - 22 mg/L - 96 h.

Toxicity to daphnia and other aquatic invertebrates: LC50 - Daphnia sp. - 16 mg/L - 48 h.

Toxicity to algae: EC50 - Green algae - 7.1 mg/L - 48 h.

Toxicity to microorganisms: no data available

Persistence and degradability

Isobutylene was degraded to 1,2-epoxybutane by pure cultures of methanotrophic bacteria(1).

Bioaccumulative potential

An estimated BCF of 35 was calculated for isobutylene(SRC), using a log Kow of 2.34(1) and a regression-derived equation(2). According to a classification scheme(3), this BCF suggests the potential for bioconcentration in aquatic organisms is moderate(SRC).

Mobility in soil

The Koc of isobutylene is estimated as 450(SRC), using a log Kow of 2.34(1) and a regression-derived equation(2). According to a classification scheme(3), this estimated Koc value suggests that isobutylene is expected to have moderate mobility in soil(SRC).

Other adverse effects

no data available

SECTION 13: Disposal considerations

Disposal methods

Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

SECTION 14: Transport information

UN Number

ADR/RID: UN1055 (For reference only, please check.)

IMDG: UN1055 (For reference only, please check.)

IATA: UN1055 (For reference only, please check.)

UN Proper Shipping Name

ADR/RID: ISOBUTYLENE (For reference only, please check.)

IMDG: ISOBUTYLENE (For reference only, please check.)

IATA: ISOBUTYLENE (For reference only, please check.)

Transport hazard class(es)

ADR/RID: 2.1 (For reference only, please check.)

IMDG: 2.1 (For reference only, please check.)

IATA: 2.1 (For reference only, please check.)

Packing group, if applicable

ADR/RID: (For reference only, please check.)

IMDG: (For reference only, please check.)

IATA: (For reference only, please check.)

Environmental hazards

ADR/RID: No

IMDG: No

IATA: No

Special precautions for user

no data available

Transport in bulk according to IMO instruments

no data available

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

European Inventory of Existing Commercial Chemical Substances (EINECS)

Listed.

EC Inventory

Listed.

United States Toxic Substances Control Act (TSCA) Inventory

Listed.

China Catalog of Hazardous chemicals 2015

Listed.

New Zealand Inventory of Chemicals (NZIoC)

Listed.

(PICCS)

Listed.

Vietnam National Chemical Inventory

Listed.

IECSC)

Listed.

Korea Existing Chemicals List (KECL)

Listed.

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

References

IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>

HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>

IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>

eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:
http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en

CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>

ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

ERG - Emergency Response Guidebook by U.S. Department of Transportation, website:
<http://www.phmsa.dot.gov/hazmat/library/erg>

Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>

ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

Other Information

Density of the liquid at boiling point: 0.605 kg/l. High concentrations in the air cause a deficiency of oxygen with the risk of unconsciousness or death. Check oxygen content before entering area. Turn leaking cylinder with the leak up to prevent escape of gas in liquid state.

Disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. We as supplier shall not be held liable for any