

Chemical Safety Data Sheet MSDS / SDS

4-methylstyrene SDS

Revision Date:2024-04-25 Revision Number:1

Section 1	Section 2	Section 3	Section 4	Section 5	Section 6	Section 7	Section 8
Section 9	Section 10	Section 11	Section 12	Section 13	Section 14	Section 15	Section 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product identifier**

Product name: 4-methylstyrene

CAS: 622-97-9

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: For R&D use only. Not for medicinal, household or other use.

Uses advised against: none

Company Identification

Company: Chemicalbook.in

Address: 5 vasavi Layout Basaveswara Nilayam Pragathi Nagar Hyderabad, India -500090

Telephone: +91 9550333722

SECTION 2: Hazards identification**Classification of the substance or mixture**

Flammable liquids, Category 3

Skin irritation, Category 2

Eye irritation, Category 2
Acute toxicity - Category 4, Inhalation
Hazardous to the aquatic environment, long-term (Chronic) - Category Chronic 2

GHS label elements, including precautionary statements

Pictogram(s)



Signal word

Warning

Hazard statement(s)

H226 Flammable liquid and vapour
H315 Causes skin irritation
H319 Causes serious eye irritation
H332 Harmful if inhaled
H411 Toxic to aquatic life with long lasting effects

Precautionary statement(s)

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P264 Wash ... thoroughly after handling.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.

Response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].
P370+P378 In case of fire: Use ... to extinguish.
P302+P352 IF ON SKIN: Wash with plenty of water/...
P321 Specific treatment (see ... on this label).
P332+P317 If skin irritation occurs: Get medical help.

P362+P364 Take off contaminated clothing and wash it before reuse.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P317 Get medical help.
P391 Collect spillage.

Storage

P403+P235 Store in a well-ventilated place. Keep cool.

Disposal

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in classification

no data available

SECTION 3: Composition/information on ingredients

Substance

Chemical name:	4-methylstyrene
Common names and synonyms:	4-methylstyrene
CAS number:	622-97-9
EC number:	210-762-8
Concentration:	100%

SECTION 4: First aid measures

Description of necessary first-aid measures

If inhaled

Fresh air, rest. Artificial respiration may be needed. Refer for medical attention.

Following skin contact

Rinse and then wash skin with water and soap.

Following eye contact

First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.

Following ingestion

Rinse mouth. Do NOT induce vomiting. Refer for medical attention .

Most important symptoms/effects, acute and delayed

Excerpt from ERG Guide 128 [Flammable Liquids (Water-Immiscible)]: Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Runoff from fire control or dilution water may cause pollution. (ERG, 2016)

Indication of immediate medical attention and special treatment needed, if necessary

If vinyl toluene gets into the eyes, wash eyes immediately with large amounts of water, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical. Vinyl toluene

SECTION 5: Firefighting measures

Suitable extinguishing media

Excerpt from ERG Guide 128 [Flammable Liquids (Water-Immiscible)]: CAUTION: All these products have a very low flash point: Use of water spray when fighting fire may be inefficient. CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective. SMALL FIRE: Dry chemical, CO₂, water spray or regular foam. LARGE FIRE: Water spray, fog or regular foam. Do not use straight streams. Move containers from fire area if you can do it without risk. FIRE INVOLVING TANKS OR CAR/TRAILER LOADS: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. ALWAYS stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. (ERG, 2016)

Specific hazards arising from the chemical

Excerpt from ERG Guide 128 [Flammable Liquids (Water-Immiscible)]: HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are

heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a (P) may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water. Substance may be transported hot. For hybrid vehicles, ERG Guide 147 (lithium ion batteries) or ERG Guide 138 (sodium batteries) should also be consulted. If molten aluminum is involved, refer to ERG Guide 169. (ERG, 2016)

Special protective actions for fire-fighters

Use water spray, foam, powder, carbon dioxide. In case of fire: keep cylinder cool by spraying with water.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal protection: self-contained breathing apparatus. Ventilation. Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid in sand or inert absorbent. Then store and dispose of according to local regulations.

Environmental precautions

Ventilation. Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid in sand or inert absorbent. Then store and dispose of according to local regulations. Personal protection: self-contained breathing apparatus.

Methods and materials for containment and cleaning up

Collect and arrange disposal. Keep the chemical in suitable and closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.

SECTION 7: Handling and storage

Precautions for safe handling

NO open flames. Above 52.8°C use a closed system, ventilation and explosion-proof electrical equipment. Handling in a well ventilated place. Wear suitable protective clothing. Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Use non-sparking tools. Prevent fire caused by electrostatic discharge steam.

Conditions for safe storage, including any incompatibilities

Separated from strong oxidants and strong acids. Well closed. Keep in a well-ventilated room. Store only if stabilized.

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational Exposure limit values

MAK: 98 mg/m³, 20 ppm; peak limitation category: I(2); pregnancy risk group: D.TLV (see Notes)

Biological limit values

no data available

Appropriate engineering controls

Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Set up emergency exits and the risk-elimination area.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Wear safety spectacles.

Skin protection

Protective gloves.

Respiratory protection

Use ventilation, local exhaust or breathing protection.

Thermal hazards

no data available

SECTION 9: Physical and chemical properties and safety characteristics

Physical state:	P-methylstyrene is a clear colorless liquid with an aromatic odor. Usually shipped with an inhibitor such as tert-butyl catechol added May polymerize if contaminated or subjected to heat. If polymerization takes place inside a closed container, the container may rupture violently. Vapors irritate the mucous membranes. Less dense than water and insoluble in water. Hence floats on water. Used in making plastics, especially as a monomer for polyesters.
Colour:	no data available
Odour:	no data available
Melting point/freezing point:	311°C(lit.)
Boiling point or initial boiling point and boiling range:	170-175°C(lit.)
Flammability:	Flammable. Heating will cause rise in pressure with risk of bursting.
Lower and upper explosion limit/flammability limit:	no data available
Flash point:	46°C
Auto-ignition temperature:	959°F
Decomposition temperature:	no data available
pH:	no data available
Kinematic viscosity:	0.0020986 Pa-s (liquid) @ 239.02 K
Solubility:	Soluble in benzene
Partition coefficient n-octanol/water:	log Kow= 3.35
Vapour pressure:	<1 mm Hg (20 °C)

Density and/or relative density:	0.895g/mL at 20°C
Relative vapour density:	(air = 1): 4.1
Particle characteristics:	no data available

SECTION 10: Stability and reactivity

Reactivity

The substance may polymerize due to warming. This generates fire or explosion hazard. Reacts with strong oxidants and strong acids.

Chemical stability

no data available

Possibility of hazardous reactions

The vapour is heavier than air. P-METHYLSTYRENE may react vigorously with strong oxidizing agents. May react exothermically with reducing agents to release hydrogen gas. In the presence of various catalysts (such as acids) or initiators, may undergo exothermic addition polymerization reactions. May undergo autoxidation upon exposure to the air to form peroxides. These peroxides and polyperoxides are usually extremely unstable and liable to detonation. The peroxidation of butadiene has been involved in several serious industrial accidents.

Conditions to avoid

no data available

Incompatible materials

Incompatible with oxidizing agents, catalysts for vinyl polymerization, such as peroxides, strong acids, aluminum chloride. Vinyl toluene

Hazardous decomposition products

no data available

SECTION 11: Toxicological information

Acute toxicity

Oral: LD50 Rat single oral para-isomer mixture 4 g/kg

Inhalation: no data available

Dermal: no data available

Skin corrosion/irritation

no data available

Serious eye damage/irritation

no data available

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

STOT-single exposure

The substance is irritating to the eyes, skin and respiratory tract. The substance may cause effects on the central nervous system.

STOT-repeated exposure

Repeated or prolonged contact with skin may cause dermatitis. The substance defats the skin, which may cause dryness or

cracking. The substance may have effects on the liver and kidneys. This may result in tissue lesions.

Aspiration hazard

A harmful contamination of the air will be reached rather slowly on evaporation of this substance at 20°C.

SECTION 12: Ecological information

Toxicity

Toxicity to fish: no data available

Toxicity to daphnia and other aquatic invertebrates: no data available

Toxicity to algae: no data available

Toxicity to microorganisms: no data available

Persistence and degradability

no data available

Bioaccumulative potential

A BCF of 32 in goldfish was measured for 4-vinyltoluene(1). According to a classification scheme(2), this BCF suggests the potential for bioconcentration in aquatic organisms is moderate(SRC).

Mobility in soil

Using a structure estimation method based on molecular connectivity indices(1), the Koc for 4-vinyltoluene can be estimated to be 840(SRC). According to a classification scheme(2), this estimated Koc value suggests that 4-vinyltoluene is expected to have low mobility in soil(SRC).

Other adverse effects

no data available

SECTION 13: Disposal considerations

Disposal methods

Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

SECTION 14: Transport information

UN Number

ADR/RID: UN2618 (For reference only, please check.)

IMDG: UN2618 (For reference only, please check.)

IATA: UN2618 (For reference only, please check.)

UN Proper Shipping Name

ADR/RID: VINYLTOLUENES, STABILIZED (For reference only, please check.)

IMDG: VINYLTOLUENES, STABILIZED (For reference only, please check.)

IATA: VINYLTOLUENES, STABILIZED (For reference only, please check.)

Transport hazard class(es)

ADR/RID: 3 (For reference only, please check.)

IMDG: 3 (For reference only, please check.)

IATA: 3 (For reference only, please check.)

Packing group, if applicable

ADR/RID: III (For reference only, please check.)

IMDG: III (For reference only, please check.)

IATA: III (For reference only, please check.)

Environmental hazards

ADR/RID: Yes

IMDG: Yes

IATA: Yes

Special precautions for user

no data available

Transport in bulk according to IMO instruments

no data available

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

European Inventory of Existing Commercial Chemical Substances (EINECS)

Listed.

EC Inventory

Listed.

United States Toxic Substances Control Act (TSCA) Inventory

Listed.

China Catalog of Hazardous chemicals 2015

Listed.

New Zealand Inventory of Chemicals (NZIoC)

Listed.

(PICCS)

Not Listed.

Vietnam National Chemical Inventory

Listed.

IECSC)

Listed.

Korea Existing Chemicals List (KECL)

Listed.

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

References

IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>

HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>

IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>

eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website: http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en

CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>

ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>

Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>

ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

Other Information

See ICSC 0514.

Disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. We as supplier shall not be held liable for any